

White gloss polymeric vinyl featuring Spandex's "PerfectApply" technology and a permanent, solvent-based adhesive. This material, which is a milestone in terms of ImagePerfect printable polymeric vinyls, has been specifically designed for digital printing on large-format inkjets and is suitable for printing with eco solvent and solvent inks as well as UV-cured inks.

IP 2503PA Plus

IP 2503PA Plus features specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure long-term outdoor durability and also incorporates Spandex's "PerfectApply", bubble-free technology to facilitate application. IP 2503PA Plus is intended for indoor and outdoor applications such as markings and decorations and vehicle graphics. This 'Plus' version incorporates a film and liner combination that manifests itself as a state-of-the-art product that will afford much greater levels of printed output than was the case with the 'classic' version of the product. It also incorporates a B1 fire rating. Laminate: IP 2810-101, IP 2810-200 or ImagePerfect™ water-based liquid laminate with UV protection.

| Specifications | |
|------------------------|--|
| DESCRIPTION | Polymeric vinyl |
| COLOUR | White gloss |
| FACE FILM THICKNESS | 70μ |
| WEIGHT | N/A |
| ADHESIVE | Solvent acrylic permanent |
| ADHESIVE STRENGTH | 20N / 25mm (Finat TM 1/24h) |
| RELEASE PAPER | PE-coated silicone paper, 140g / m ² |
| TEMPERATURE RANGE | -30°C to +90°C |
| DURABILITY (UNPRINTED) | Up to 7 years |
| FLAME RETARDANCY | B1 |
| SHELF LIFE | 2 years, 20°C / 50% humidity |
| RECOMMENDATION | For optimum quality, please ensure that the media feed adjustment has been completed for this material |

© October 2009 Spandex Group. Technical specifications subject to change without prior notice. All trademarks mentioned are property of their respective owners. Output may vary depending on the type of print data/file, application, media, environmental conditions, print speed, or other variables.